

# BGJ55-0920

# DOM 27" X 38"

This is a battery-operated product. 1 flyer (00001-2908G8) is required to be placed inside the packaging.

## INSTRUCTIONS

## LINE BOTTOM UP ALONG FLOOR



### WALL TRACKS® SUPER LOOP CHASE RACE™

Keep these instructions for future reference as they contain important information.

**START HERE:** Please read all instructions before beginning assembly and set-up.

#### YOU WILL NEED:

- Low-adhesive tape such as painter's tape or masking tape
- Approximately 4 feet (120 cm) by 4 feet (120 cm) of wall space
- 30 minutes



**CONTENTS:**

Requires 4 "D" size (LR20) alkaline batteries, not included. Dispose of batteries safely.

**1 PRESS FIRMLY FOR 30 SECONDS APPLY LABELS**

**2 BATTERY INSTALLATION**

- Unscrew the battery cover with a Phillips head screwdriver (not included).
- Install 4 "D" size (LR20) alkaline batteries (not included) in the orientation (+/-) shown.
- Replace battery cover and tighten screws.
- For longer life use alkaline batteries.
- Replace batteries when booster can no longer propel car through the track set.
- When exposed to an electrostatic source, the product may malfunction. To resume normal operation, remove and re-install the batteries.

I= ON  
O=OFF

**3 HANG TEMPLATE**

Line template up with floor and tape to wall. Template should lay flat and level against the wall.

**NOTE TO PARENTS:** Before applying Command® Strips make sure the wall surface is clean and dry. If cleaning is necessary 3M recommends using isopropyl rubbing alcohol. Do not use household cleaners.

Press bracket firmly for 30 seconds.

**LINE BOTTOM UP ALONG FLOOR**

**4 PREPARE BRACKETS**

There are 5 flat brackets and 6 Command® Strips (1 extra strip).

Separate strips. Remove red-printed liner from Command® Strips and apply to back of brackets as shown. Make sure the strip tab is accessible for future removal.

**NOTE:** Apply strips to surfaces above 50°F (10°C). Adhesive could lose adhesion above 105°F (40°C).

**CAUTION:** DO NOT use with wallpaper. May not adhere well to vinyl surfaces. DO NOT hang items over beds.

**NOTE: DO NOT PULL BRACKET OFF WALL** without reading removal instructions in step 10.

**5 HANG BRACKETS**

Remove black-printed liner from Command® Strips and attach each bracket into the designated notch of the template as shown.

Bracket should not overlap the template.

**Press bracket firmly onto wall and hold, pressing for 30 seconds.**

**6 REMOVE TEMPLATE**

Once all brackets are firmly attached, remove template.

**NOTE:** For optimal adhesion performance 3M recommends waiting 1 hour before adding weight to Command® Strips.

Press bracket firmly for 30 seconds.

**7 ASSEMBLE TRACK PIECES** Pre-assemble pieces as shown.

Press bracket firmly for 30 seconds.

SEE REVERSE FOR STEPS 8-10

## FLUSH WITH FLOOR

## SEE OTHER SIDE FOR STEPS 1-7

**8 HANG TRACK ON WALL**

**OPERATING TIPS:**

- To ensure the car travels smoothly, adjust track edges at connection points as shown. This prevents the car from crawling into track edges.
- To ensure the car travels smoothly, adjust track edges at connection points as shown. This prevents the car from crawling into track edges.

**9 LET'S PLAY!**

**1. Power ON (I).** I= ON, O=OFF

**2. Load car.** Push lever down to race car around the double loops.

**3. Open the gate.** Push diverter to release car from the track.

**10 REATTACHING & REMOVAL**

Remove track pieces from wall prior to removing brackets.

Mounting brackets are designed to break away from the set without causing surface damage. If mounting plate separates from bracket, snap bracket back into place.

To remove brackets from the wall entirely:

- NEVER pull strip towards you.
- Hold bracket gently to prevent it from snapping fingers. DO NOT press against wall.
- Grab tab on Command® Strip and SLOWLY STRETCH STRAIGHT DOWN ALONG WALL AT LEAST 12 INCHES until bracket and strip release.

Purchase medium Command® Refill Strips to reapply to your wall.

**CONNECT**

Connects to BGJ25 SUPER START JUMP RACE™ and BGJ26 SUPER LAUNCH SPEED TRACK™ (sold separately, subject to availability).

Not included: BGJ25, BGJ26

Detach track from base: BGJ55, BGJ26

Command® Strips are a product of 3M. For further information visit [command.com](http://command.com)

**NOTE:** Apply strips to surfaces above 50°F (10°C). Adhesive could lose adhesion above 105°F (40°C).

**CAUTION:** DO NOT use with wallpaper. May not adhere well to vinyl surfaces. DO NOT hang items over beds.

3M and Command are trademarks of 3M. © 2013 3M. All Rights Reserved.

Hot Wheels is a trademark of Mattel. © 2013 Mattel. All Rights Reserved. Mattel, Inc., 636 Grand Avenue, East Aurora, NY 14052, U.S.A. Consumer Relations: 1-800-521-8687. Mattel U.K. Ltd., Vauxhall Business Park, Brierleyford, Leicestershire LE19 1FJ, England. Mattel Australia Pty. Ltd., Richmond, Victoria 3121 Consumer Advisory Service - 1300 735 312. Mattel East Asia Ltd., Room 1106, South Tower, World Finance Centre, Harbour City, Transamerica, HK. China, Donghai & Donghai Toys, Mainland China. Mexico SCA, P.O. Box 199202, Dallas, TX 75219, U.S.A. 13th Floor, Mexico Lien Hoe, Petrusaria Tropicana Golf Country Resort, 47410 Puz. Tel: 03-78803817. Fax: 03-78803867.

