

HOT WHEELS WALL TRACKS
AUTO MOTION SPEEDWAY™ HANGING TEMPLATE

4+ FOR INSTRUCTIVE VIDEOS AND MORE GO TO WWW.HOTWHEELS.COM/WALLTRACKS

Press bracket firmly for 30 seconds.
TAB FACES UP
UPSIDE DOWN COMMAND™ STRIP GOES HERE!

Keeps with **Command™ STRIPS**

Keep these instructions for future reference as they contain important information.

CONTENTS:

YOU WILL NEED: Low-adhesive tape such as painter's tape or masking tape. Approximately 3 feet by 4 feet of open wall space. 20 minutes.

START HERE: Please read all instructions before beginning assembly and set-up.

1 HANG TEMPLATE
 Lie template flat and level against wall and tape as shown. Top of template should align with the height of the child.
NOTE TO PARENTS: Before applying Command™ Strips make sure the wall surface is clean and dry. If cleaning is necessary 3M recommends using isopropyl rubbing alcohol. Do not use household cleaners.

2 PREPARE BRACKETS
 Red Printing = On Bracket Black Printing = On Wall
 There are 2 lettered brackets (Marked A - B), 3 flat brackets, and 6 Command™ Strips (1 extra strip). Separate strips. Remove red-printed liner from Command™ Strips and apply to back of brackets as shown. Make sure the strip tab is accessible for future removal.
NOTE: DO NOT PULL BRACKET OFF WALL without reading removal instructions in step 8.
 NOTE: Apply strips to surfaces above 50°F (10°C). Adhesive could lose adhesion above 105°F (40°C).
 CAUTION: DO NOT use with wallpaper. May not adhere well to vinyl surfaces. DO NOT hang items over back.

3 HANG BRACKETS
 Remove black-printed liner from Command™ Strips and attach each bracket into the designated notch of the template as shown. Bracket should not overlap the template. Press bracket firmly onto wall and hold, pressing for 30 seconds.
 Red arrow should line up with arrow on bracket.
INCORRECT CORRECT

4 REMOVE TEMPLATE
 Once all brackets are firmly attached with red arrows correctly oriented, remove template.
 Note: For optimal adhesion performance 3M recommends waiting 1 hour before adding weight to Command™ Strips.

5 ASSEMBLE TRACK PIECES Pre-assemble pieces as shown.

1. Press bracket firmly for 30 seconds.

2. Press bracket firmly for 30 seconds.

3. **Brackets should NOT overlap template**
PRESS FIRMLY FOR 30 SECONDS

4. **BACK VIEW**

5. Press bracket firmly for 30 seconds.

6. Press bracket firmly for 30 seconds.

SEE REVERSE FOR STEPS 6-8.

SEE OTHER SIDE FOR STEPS 1-5

6 HANG TRACK ON WALL
 Once brackets are mounted and TEMPLATE IS REMOVED FROM WALL, attach track pieces as shown.

1.

2.

3.

4.

5.

6.

7.

7 LET'S PLAY!

1. Move arrow to starting point as shown.

2. Load cars.

3. Spin the wheel gently to launch cars.

Send your cars in different directions!

8 REATTACHING & REMOVAL

Mounting brackets are designed to break away from the set without causing surface damage. If mounting plate separates from bracket, snap bracket back into place.

To remove brackets from the wall entirely:
 1. NEVER pull strip towards you.
 2. Hold bracket gently to prevent it from snapping fingers. DO NOT press against wall.
 3. Grab tab on Command™ Strip and SLOWLY STRETCH STRAIGHT DOWN ALONG WALL AT LEAST 12 INCHES until bracket and strip release.

Purchase medium Command™ Refill Strips to reapply to your wall.

CONNECT
 Create your own set-ups with other Wall Tracks™ sets.