

TECH C TRAX

Cool cars, games and more!

• Mattel, Inc., El Segundo, CA 90245 U.S.A. Consumer Affairs 1 (800) 524-TOYS.

1 CONTRACT

• Mattel East Asia Ltd., Room 1106, South Tower, World Finance Centre, Harbour City, Tsimshatsui, HK, China. <u>Mattel U.K. Ltd., Vanwall Business Park, Maidenhead SL6 4UB. Helpline 01628500303.</u>
Mattel Australia Pty., Ltd., Richmond, Victoria. 3121.Consumer Advisory Service - 1300 135 312.











All track TECH TH to lock th

TECH TRAX M Building Basics




All track connections lock together with the *TECH TRAX*[™] system. Be sure tabs insert fully to lock tracks together properly as shown.

To unlock tracks, press in on locking tabs and pull apart at the same time as shown.




Clips attach to tracks as shown. Notches on clips align with tabs on tracks to lock in proper position.





Press guardrails into clips until they snap and lock.
















14" (35.5 cm) Guardrail

20" (51 cm) Guardrail





RETER PLAY

TROUBLESHOOTING AND TIPS

STO & GO

All the pieces of your track set can be easily stored inside the unique STO & GO™ package! Place larger items back in canister first.



to carefully flex the ends outward, so that it won't impede the vehicles movement.



connecting the track pieces of TECH TRAX[™], to existing Hot Wheels[®] track.



To use the 45/90/T-Joints, simply slide a Rod into the open face of the joint, and then close over the cover element. (Note: Be sure the "Joint Key" is rotated into its "open" position.) To lock its position on the rod, rotate the Joint Key 90 degrees.

Fine tuning of the set is required to yield optimum performance.



simply slide it onto one of the Rod pieces. (Note: Be sure the "Locking Key" is in the open position.)

Position along the rod where desired, and then turn the Lock key to secure.



o attach the track, take the section where two tracks are joined, and simply slide into the rotating clip unit.

By loosening the Locking Key, you can now set the angle of the track as you desire.



To remove the track from the Rotating Clip, simply squeeze its ends outward, and pull track out of the groove.






THE ADVANCED CONSTRUCTION SYSTEM FOR ULTIMATE STUNTS

R

RRX™







Cool cars, games and more!

Mattel, Inc., El Segundo, CA 90245 U.S.A. Consumer Affairs 1 (800) 524-TOYS.
<u>Mattel U.K. Ltd., Vanwall Business Park, Maidenhead SL6 4UB. Helpline. 01628500303.</u>
Mattel Australia Pty., Ltd., Richmond, Victoria. 3121.Consumer Advisory Service - 1300 135 312.

 Mattel East Asia Ltd., Room 1106, South Tower, World Finance Centre, Harbour City, Tsimshatsui, HK, China.
Diimport & Diedarkan Oleh: Mattel SEA Ptd Ltd.(993532-P) Lot 13.5, 13th Floor, Menara Lien Hoe, Persiaran Tropicana Golf Country Resort, 47410 PJ. Tel:03-78803817, Fax:03-78803867.










TECH TRAX M Builaing Basics 🗺





All track connections lock together with the *TECH TRAX*[™] system. Be sure tabs insert fully to lock tracks together properly as shown.

To unlock tracks, press in on locking tabs and pull apart at the same time as shown.



Clips attach to tracks as shown. Notches on clips align with tabs on tracks to lock in proper position.






Press guardrails into clips until they snap and lock.




















RETER PLAY

TROUBLESHOOTING AND TIPS

To use the 45/90/T-Joints, simply slide a Rod into the open face of the joint, and then close over the cover element. (Note: Be sure the "Joint Key" is rotated into its "open" position.) To lock its position on the rod, rotate the Joint Key 90 degrees.

Fine tuning of the set is required to yield optimum performance.

STO & GO™







Where Guardrail ends, be sure to carefully flex the ends outward, so that it won't impede the vehicles movement.



adaptor for connecting the track pieces of TECH TRAX[™], to existing Hot Wheels[®] track.



To use the 3XL, simply slide it onto one of the Rod pieces. (Note: Be sure the "Locking Key" is in the open position.)

Position along the rod where desired, and then turn the Lock key to secure.



By loosening the Locking Key, you can now set the angle of the track as you desire.



e rotating clip unit.

o attach the track, take the

section where two tracks are joined, and simply slide into



To remove the track from the Rotating Clip, simply squeeze ts ends outward, and pull track out of the groove.








Cool cars, games and more!

• Mattel, Inc., El Segundo, CA 90245 U.S.A. Consumer Affairs 1 (800) 524-TOYS. • Mattel U.K. Ltd., Vanwall Business Park, Maidenhead SL6 4UB. Helpline 01628500303 • Mattel Australia Pty., Ltd., Richmond, Victoria. 3121.Consumer Advisory Service - 1300 135 312.


• Mattel East Asia Ltd., Room 1106, South Tower, World Finance Centre, Harbour City, Tsimshatsui, HK, China. Diimport & Diedarkan Oleh: Mattel SEA Ptd Ltd. (993532-P) Lot 13.5, 13th Floor, Menara Lien Hoe, Persiaran Tropicana Golf Country Resort, 47410 PJ. Tel:03-78803817, Fax:03-78803867.



8+




TECH TRAX M Building Basics 🗺





All track connections lock together with the *TECH TRAX*[™] system. Be sure tabs insert fully to lock tracks together properly as shown.

To unlock tracks, press in on locking tabs and pull apart at the same time as shown.



Clips attach to tracks as shown. Notches on clips align with tabs on tracks to lock in proper position.





Press guardrails into clips until they snap and lock.















Congratulations! Your TECH TRAX™ FLEX LOOP™ set is complete. "You're a TECH TRAX™ Master." Now choose your car, and you're ready to test your skill!

Астерляте Сачоит 🦛



READY TO PLAY

15



Place Car here

Pull Trigger

123

Launcher has 4 speed levels, to vary the speed of your car around Flex Loop[™].

Vehicles not included.

Bottom View

Pull back cover.
Replace rubber band.



Vehicles not included.

FILISH

2 Car will climb up the loop and continue on right side track to finish point.


1 Press to release car.

AFTER PLAY

TROUBLESHOOTING AND TIPS

STO & GO™









Where Guardrail ends, be sure to carefully flex the ends outward, so that it won't impede the vehicles movement.



The T2P connector can be used as an adaptor for connecting the track pieces of TECH TRAX[™], to existing Hot Wheels[®] track.

To use the 45/90/T-Joints, simply slide a Rod into the open face of the joint, and then close over the cover element. (Note: Be sure the "Joint Key" is rotated into its "open" position.) To lock its position on the rod, rotate the Joint Key 90 degrees.

Fine tuning of the set is required to yield optimum performance.



sure the "Locking Key" is in the open position.)



Position along the rod where desired, and then turn the Lock key to secure.



joined, and simply slide into ne rotating clip unit

By loosening the Locking Key, you can now set the angle of the track as you desire.



o attach the track, take the

section where two tracks are



o remove the track from the Rotating Clip, simply squeeze its ends outward, and pull track out of the groove.







TEC TRAX

G3736-0900

THE ADVANCED CONSTRUCTION SYSTEM FOR ULTIMATE STUNTS

R

